



# 200W Single output power with PFC Function HS Series

- High efficiency, long service life and high reliability
- Output protection function: Over current/short circuit
- Ultra wide operating temperature range -25~70°C
- Long service life electrolytic capacitor
- 100% full load ageing test
- Built-in active PFC function
- No fan, quiet
- 3 years




MODEL		HS-200P-5	HS-200P-12	HS-200P-15	HS-200P-24	HS-200P-36	HS-200P-48
OUTPUT	DC Output	5V	12V	15V	24V	36V	48V
	Rated Current	36A	16.7A	13.3A	8.3A	5.6A	4.2A
	Current Range	0~36A	0~16.7A	0~13.3A	0~8.3A	0~5.6A	0~4.2A
	Ripple and Noise	50mV	120mV	150mV	200mV	200mV	200mV
	Voltage ADJ. Range	±10% of rated output voltage					
	Voltage Accuracy	±2.0%	±1.0%	±1.0%	±1.0%	±1.0%	±1.0%
	Line Regulation	±0.5%	±0.5%	±0.5%	±0.5%	±0.5%	±0.5%
	Load Regulation	±1.5%	±0.5%	±0.5%	±0.5%	±0.5%	±0.5%
	Set-up Time	<2S (230VAC input), <2S (115VAC input)					
INPUT	Hold up Time	<70ms/230VAC 15ms/115VAC					
	Voltage Range	88~264VAC					
	Frequency Range	47Hz~63Hz					
	Efficiency	79%	80%	80%	82%	82%	83%
PROTECTION	Inrush Current (Typical)	<50A@230VAC <50A@115VAC Cold start					
	Over Load	105%~135% of rated output current, hiccup mode, auto recovery					
	Over power	120%~130% of rated output current, hiccup mode, auto recovery					
ENVIRONMENT	Operating amb. Temp. & Hum.	-25°C~70°C; 25%~90%RH					
	Storage Temp. & Hum.	-40°C~85°C; 10%~95%RH					
SAFETY&EMC	Safety Standards	Reference GB4943/EN60950, UL62368-1, TUV EN62368-1					
	Withstand Voltage	Primary-Secondary:3.0KVac; Primary-PG:1.5KVac; Secondary-PG:0.5KVDC					
OTHERS	MTBF (MIL-HDBK-217F)	More than 100,000Hrs (25°C, Full load)					
	Dimension (L*W*H)	200*112*50mm					
	Packing	1kg/PCS					
	Cooling method	Cooling by free air convection					
NOTE	1. All parameters NOT specially mentioned are measured at rated input, rated load and 25°C of ambient temperature.						

Block diagram of internal mechanism



Organization size chart:



Declining curve:

