


- High efficiency, long service life and high reliability
- output protection function: Over current/short circuit
- ultra wide operating temperature range  $-20^{\circ}\text{C} \sim 70^{\circ}\text{C}$
- long service life electrolytic capacitor
- 100% full load ageing test
- no fan, quiet
- 3 years



MODEL	HS-20-5	HS-20-12	HS-20-15	HS-20-24	HS-20-36	HS-20-48	
OUTPUT	DC Output	5V	12V	15V	24V	36V	48V
	Rated Current	4A	1.7A	1.34A	0.83A	0.55A	0.42A
	Current Range	0~4A	0~1.7A	0~1.34A	0~0.83A	0~0.55A	0~0.42A
	Ripple and Noise	50mV	120mV	150mV	200mV	200mV	200mV
	Voltage ADJ. Range	±10% of rated output voltage					
	Voltage Accuracy	±2.0%	±1.0%	±1.0%	±1.0%	±1.0%	±1.0%
	Line Regulation	±0.5%	±0.5%	±0.5%	±0.5%	±0.5%	±0.5%
	Load Regulation	±1.5%	±0.5%	±0.5%	±0.5%	±0.5%	±0.5%
	Set-up Time	< 1.2S (230VAC input), < 2.5S (115VAC input)					
	Hold up Time	70ms/230VAC 15ms/115VAC					
INPUT	Voltage Range	88Vac~264Vac					
	Frequency Range	47Hz~63Hz					
	Efficiency	79%	80%	80%	82%	82%	82%
	Inrush Current (Typical)	<30A@230VAC <20A@115VAC Cold start					
PROTECTION	Over Load	105%~135% of rated output current, hiccup mode, auto recovery					
	Over power	120%~130% of rated output current, hiccup mode, auto recovery					
	Short Circuit	Long-term mode, auto recovery					
ENVIRONMENT	Operating amb. Temp. & Hum.	$-20^{\circ}\text{C} \sim 70^{\circ}\text{C}$ ; 25%~90%RH					
	Storage Temp. & Hum.	$-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ ; 10%~95%RH					
SAFETY & EMC	Safety Standards	Reference GB4943/EN60950, UL62368-1, TUV EN62368-1					
	Withstand Voltage	Primary-Secondary:3.0KVac; Primary-PG:1.5KVac; Secondary-PG:0.5KVDC					
OTHERS	MTBF (MIL-HDBK-217F)	More than 100,000Hrs (25°C, Full load)					
	Dimension (L*W*H)	116*50*27mm					
	Packing	300g/PCS					
	Cooling method	Cooling by free air convection					
NOTE	1. All parameters NOT specially mentioned are measured at rated input, rated load and 25°C of ambient temperature.						

Block diagram of internal mechanism



Declining curve:

